

Philips LCD monitor with SmartImage lite

Ultra Narrow Bezel

27" / 68.6cm MHL

274E5QHSB

Vibrant images with AH-IPS display

with Ultra Narrow Bezel, MHL

This attractive Philips display with ultra narrow bezel and AHIPS screen gives you awesome, vibrant color images. Mobile HD link allows you to mirror your Smartphone.

Entertainment with Mobile HD Link

- MHL technology for enjoying mobile content on big screen
- $\bullet\,$ Optional MHL cable allows for HD video audio playback
- Charge your mobile device while watching movie
- HDMI-ready for Full HD entertainment

Awesome picture quality

- · AH-IPS display gives awesome images with wide viewing angle
- 16:9 Full HD display for best viewing experience
- TrueVision ensures lab quality images
- SmartImage Lite for an enhanced LCD viewing experience

Stylish design

- Minimalistic looks with Ultra Narrow Bezel
- · Superb glossy and texture finish
- VESA mount for convenience



Highlights

MHL technology



Mobile High Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to high-definition displays. An optional MHL cable allows you to simply connect your MHL capable mobile device to this large Philips MHL display, and watch your HD videos come to life with full digital sound. Now not only you can enjoy your mobile games, photos, movies, or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power half way.

AH-IPS technology

This latest Philips display uses advanced AH-IPS panels utilizing improved structure resulting in superior color reproduction, response time and power consumption compared to other wide view angle panels. Unlike standard TN panels, AH-IPS panels exhibit least amount of Gamma fluctuation and therefore are able to show consistent color even at 178/178 degrees and in pivot mode. With remarkable performance, it is best suited for applications demanding color accuracy and consistent brightness at all times like photo retouching, graphics applications and web browsing.

Ultra Narrow Bezel

Utilizing latest technology panels, the new Philips displays are designed with minimalistic approach by limiting the outer bezel thickness to about 2.5mm. Combined with in-panel black matrix strip of around 9mm, the overall bezel dimensions are reduced significantly allowing for minimal distractions and maximum viewing size. Especially suited for multi-display or tiling setup like gaming, graphics design and professional applications, the Ultra narrow bezel display gives you the feeling of using one large display.

SmartImage Lite

SmartImage Lite is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage Lite dynamically enhances the contrast, color saturation and sharpness of images and videos for ultimate display performance - all in real time with the press on a single button.

HDMI Ready



A HDMI-ready device has all the required hardware to accept High-Definition
Multimedia Interface (HDMI) input, high quality digital video and audio signals all transmitted over a single cable from a PC or any number of AV sources including set-top boxes, DVD players and A/V receivers and video cameras.

16:9 Full HD



The Full HD screen has the widescreen resolution of $1920 \times 1080p$. This is the highest resolution of HD sources for the best possible picture quality. It is fully future proof as it supports 1080p signals from all sources, including the most recent like Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colors.

TrueVision



TrueVision is a proprietary Philips technology that uses advanced algorithm for testing and aligning monitor display which gives you the ultimate display performance that is 4 times more stringent than Windows sRGB requirements. Only Philips ensures each and every monitor that leaves the factory is fine tuned with this process so you can get consistent color and picture quality.





















Specifications

Picture/Display

- LCD panel type: AH-IPS LCD
- · Backlight type: W-LED system
- Panel Size: 27 inch / 68.6 cm
- Effective viewing area: 597.89 (H) x 336.31 (V)
- Aspect ratio: 16:9
- Optimum resolution: 1920 x 1080 @ 60Hz
- SmartResponse (typical): 5 ms (Grey to Grey)
- Brightness: 250 cd/m²
- Contrast ratio (typical): 1000:1
- SmartContrast: 20,000,000:1
- Pixel pitch: 0.311 x 0.311 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- · Picture enhancement: SmartImage Lite
- Display colors: 16.7 M
- Scanning Frequency: 30 -83 kHz (H) / 56 -75 Hz (V)
- MHL: 1080p@30Hz
- sRGB

Connectivity

- Signal Input: HDMI (digital, HDCP), MHL-HDMI (digital, HDCP), VGA (Analog)
- Sync Input: Separate Sync, Sync on Green
- · Audio In/Out: HDMI audio out

Convenience

- User convenience: Power On/Off, Menu, 4:3 / Wide, Input, SmartImage lite
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukranian
- · Other convenience: Kensington lock, VESA mount (100×100mm)
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 7, Windows 8

Stand

• Tilt: -5/20 degree

Power

- On mode: 24.1 W (EnergyStar 6.0 test method)
- Standby mode: 0.5 W (typ.)
- Off mode: 0.3 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: External, 100-240VAC, 50-60Hz

Dimensions

- Product with stand (mm): $622 \times 470 \times 237$ mm
- Product without stand (mm): $622 \times 375 \times 46 \text{ mm}$
- Packaging in mm (WxHxD): 667 x 546 x 106 mm

Weight

- Product with stand (kg): 5.10 kg
- Product without stand (kg): 4.88 kg
- Product with packaging (kg): 7.14 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
 Temperature Range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 30,000 hour(s)

Sustainability

- Environmental and energy: EnergyStar 6.0, EPEAT Silver, RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

• Regulatory Approvals: BSMI, CE Mark, uETLus, FCC Class B, GOST, SASO, SEMKO, TCO 6.0, TUV/ISO9241-307, WEEE

Cabinet

- Color: Black Cherry / Black
- Finish: Glossy



Issue date 2013-04-04

Version: 4.1.1

12 NC: 8670 000 99691 EAN: 87 12581 67547 9 © 2013 Koninklijke Philips Electronics N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com

- Requires optional MHL certified mobile device and MHL cable. (not included) Please check with your MHL device vendor for compatibility.
- * Standby/Off energy saving of ErP is not applicable for the MHL charging functionality
- word mark / trademark and related patents on technologies belong to their respective owners.